Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-034-6442

# Section Quantity:

1

Body Style:

Rectangular w/mounting holes

Reliability Indicator:

Not established

**Terminal Length:** 

4.000 inches

### Mounting Hole Diameter:

0.093 inches

Shaft Diameter:

0.060 inches

Shaft Length:

0.030 inches

Body Length:

## 0.500 inches

**Body Width:** 

0.187 inches

**Body Height:** 

0.500 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

### Maximum Starting Torque:

7.50 inch-ounces

Maximum Running Torque:

7.50 inch-ounces

### Lateral Distance Between Mounting Hole Centers:

Between 0.515 inches and 0.530 inches

### **Mounting Facility Quantity:**

2

Terminal Location: Rear end Mounting Method: Unthreaded hole

Features Provided:

Humidity proof

**Electrical Resistance Per Section:** 

50.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

15120.0



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 200.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -50.0/+50.0 single section **Power Dissipation Rating Per Section In Watts:** 1.5 free air single section **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Actuator Travel Control Feature:** Continuous motion Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 100.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 wire lead Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A002a0