Precision Nonwire Wound Variable Resistor - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5905-01-035-1879

## Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

### Terminal Length:

Between 1.240 inches and 1.260 inches

### Mounting Hole Diameter:

0.093 inches

#### Shaft Diameter:

0.125 inches

Shaft Length:

Between 0.060 inches and 0.080 inches

#### **Body Length:**

Between 1.240 inches and 1.260 inches

**Body Width:** 

### 0.195 inches

**Body Height:** 

0.325 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

#### Center To Center Distance Between Terminals:

Between 0.890 inches and 0.910 inches

#### Lateral Distance Between Mounting Hole Centers:

Between 0.990 inches and 1.010 inches

#### **Mounting Facility Quantity:**

2

#### **Terminal Location:**

Lower adjacent side single row

#### **Mounting Method:**

Unthreaded hole

#### **Electrical Resistance Per Section:**

100.000 ohms single section

# Center To Center Distance Between Center Terminal And Outside Terminal:

Between 0.190 inches and 0.210 inches

# Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-10.0/+10.0 single section

### Power Dissipation Rating Per Section In Watts:

0.5 free air single section

# Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section



Precision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0