Nonprecision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-035-3479

Section Quantity:

2

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

2.250 inches

Body Diameter:

0.500 inches

Shaft Diameter:

0.187 inches

Shaft Length:

1.125 inches

Mounting Bushing Length:

0.250 inches

Body Length:

1.125 inches

Overall Diameter:

0.670 inches

Undercut Diameter:

0.1248 inches

Shaft Style:

Round, stepped

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

300.0

Maximum Starting Torque:

3.00 inch-ounces

Maximum Running Torque:

1.00 inch-ounces

Nonturn Device Location:

At 12 oclock

Nonturn Device Radius:

0.200 inches

Shaft End Play:

0.00600 inches

Shaft Runout:

0.004 inches

Lateral Runout:

0.003 inches



Pilot Diameter Runout:
0.00300 inches
Shaft Radial Play:
0.001 inches
End Application:
An/apr-38
Undercut Length:
0.281 inches
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
10.000 kilohms all sections
Rotary Actuator Travel In Angular Deg:
345.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 all sections
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
100.0 all sections
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-250.0/+250.0 all sections
Power Dissipation Rating Per Section In Watts:
0.25 free air all sections
Function Conformity Per Section:
All sections independent linearity
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 all sections
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
All sections linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 all sections
Special Features:
Inner shaft has a flat length 0.281 in. And a flat height 0.107 in.
Terminal Type And Quantity:

6 tab, solder lug

NSN 5905-01-035-3479

Nonprecision Wire Wound Variable Resistor - Page 3 of 3



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0