

View Online at <https://aerobasegroup.com/nsn/5905-01-035-5633>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

3.812 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.375 inches

Mounting Bushing Length:

0.250 inches

Body Length:

4.125 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

10800.0

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.531 inches

Fragility Factor:

Moderately rugged

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Features Provided:

Humidity proof

Electrical Resistance Per Section:

135.0 ohms single section

Rotary Actuator Travel In Angular Deg:

10800.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0/+50.0 single section

Power Dissipation Rating Per Section In Watts:

1.5 free air single section

Resistance Tolerance Per Section In Percent:

-2.0/+2.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

55.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0