NSN 5905-01-035-5635

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-035-5635 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.75000 inches Pilot Length: 0.06200 inches **Undercut Diameter:** 0.750 inches **Undercut Width:** 0.06200 inches **Body Diameter:** 0.891 inches **Shaft Diameter:** Between 0.1245 inches and 0.1248 inches **Shaft Length:** 0.500 inches **Body Length:** 0.500 inches **Mounting Lip Diameter:** 0.87500 inches **Mounting Lip Depth:** 0.06200 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 342.0 **Maximum Starting Torque:** 0.50 inch-ounces **Maximum Running Torque:** 0.50 inch-ounces **Shaft Runout:**

0.001 inchesLateral Runout:0.002 inches

NSN 5905-01-035-5635

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 3



Pilot Diameter Runout:
0.00100 inches
Shaft Radial Play:
0.001 inches
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
5.0 kilohms single section
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:
171.0 single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.50/+0.50 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-150.0/+300.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
1 single section
Tap Location Tolerance Per Section:
-1.0/+1.0 degrees angular rotation single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Terminal Type And Quantity:
4 turret
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No

NSN 5905-01-035-5635

Nonprecision Nonwire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0