

View Online at <https://aerobasegroup.com/nsn/5905-01-035-6135>

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

Between 0.49950 inches and 0.50000 inches

Pilot Length:

0.04000 inches

Undercut Diameter:

Between 0.624 inches and 0.625 inches

Undercut Width:

0.06200 inches

Body Diameter:

0.750 inches

Shaft Diameter:

Between 0.1245 inches and 0.1248 inches

Shaft Length:

0.375 inches

Body Length:

0.625 inches

Mounting Lip Diameter:

0.75000 inches

Mounting Lip Depth:

0.06200 inches

Shaft Style:

Round

Shaft Bearing Type:

Bearing

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

340.0

Maximum Starting Torque:

0.50 inch-ounces

Maximum Running Torque:

0.40 inch-ounces

Nonturn Device Location:

At 6 oclock

Nonturn Device Radius:

0.281 inches

Shaft End Play:

0.00500 inches

Shaft Runout:

0.002 inches

Lateral Runout:

0.002 inches

Pilot Diameter Runout:

0.00100 inches

Shaft Radial Play:

0.001 inches

Mechanical Backlash In Deg Angular Rotation:

0.5

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring

Electrical Resistance Per Section:

10.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

360.0

Function Conformity Tolerance Per Section:

-1.00/+1.00 single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Power Dissipation Rating Per Section In Watts:

0.7 free air single section

Function Conformity Per Section:

Single section independent linearity

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

Single section linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0