NSN 5905-01-035-6699

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-035-6699
Section Quantity:
1
Body Style:
Cylindrical
Reliability Indicator:
Not established
Overall Length:
0.906 inches
Terminal Length:
0.547 inches
Body Diameter:
0.500 inches
Body Length:
0.359 inches
Overall Diameter:
0.500 inches
Actuator Type:
Flush drive with slot-hole
Effective Electrical Rotation In Deg Angular Rotation:
295.0
Center To Center Distance Between Terminals:
0.200 inches
Fragility Factor:
Moderately delicate
Terminal Location:
Rear end
Mounting Method:
Terminal
Features Provided:
Humidity proof
Electrical Resistance Per Section:
5.0 percent, rated amperes c and better flooring
Rotary Actuator Travel In Angular Deg:
295.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Resistance Tempurature Characteristic Range Per Section In Percent:
+0.0/+5.5 -55 degrees celsius single section and +0.0/+3.0 -25 degrees celsius single section and +0.0/+1.5 0 degrees celsius single section
and -2.0/+2.0 85 degrees celsius single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

0.25 7th secondary quality

Power Dissipation Rating Per Section In Watts:

100.0 single section

NSN 5905-01-035-6699

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:
-20.0/+20.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
50.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No