Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-036-0832

## Section Quantity: 1 **Body Style:** Cylindrical **Reliability Indicator:** Not established **Body Diameter:** 0.781 inches **Body Length:** 0.391 inches Actuator Type: Flush drive with slot-hole Effective Electrical Rotation In Deg Angular Rotation: 270.0 **Fragility Factor:** Moderately delicate **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Tab **Electrical Resistance Per Section:** 5.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 270.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 105.0 single section **Power Dissipation Rating Per Section In Watts:** 2.0 free air single section **Resistance Tolerance Per Section In Percent:** -20.0/+20.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 55.0 single section Standard Taper Curve Per Section: A single section **Terminal Type And Quantity:** 3 pin clamp Shelf Life: N/a Unit Of Measure: ---

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A002a0