NSN 5905-01-036-2798

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-036-2798

Section Quantity:
1
Body Style:
Cylindrical
Reliability Indicator:
Not established
Overall Length:
0.500 inches
Body Diameter:
0.594 inches
Mounting Hole Diameter:
Between 0.053 inches and 0.057 inches
Mounting Slot Width:
Between 0.054 inches and 0.058 inches
Body Length:
0.259 inches
Actuator Type:
Integral knob
Effective Electrical Rotation In Deg Angular Rotation:
260.0
Mounting Facility Quantity:
4
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Slot and unthreaded hole
Electrical Resistance Per Section:
2.5 kilohms single section
Rotary Actuator Travel In Angular Deg:
Between 255.0 and 265.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
0.2 free air single section
Resistance Tolerance Per Section In Percent:
-20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
55.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
O take a saldan kun

2 tab, solder lug

NSN 5905-01-036-2798

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

A002a0