## NSN 5905-01-036-3928

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-036-3928 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 1.563 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.344 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 1.281 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 300.0 **Nonturn Device Location:** At 6 oclock **Nonturn Device Radius:** 0.500 inches **Fragility Factor:** Rugged **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 

25.0 ohms single section

**Rotary Actuator Travel In Angular Deg:** 

300.0

## NSN 5905-01-036-3928

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 340.0 single section **Power Dissipation Rating Per Section In Watts:** 25.0 free air single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 2 tab, solder lug Shelf Life: N/a **Unit Of Measure: Demilitarization:** No