NSN 5905-01-036-5526

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-036-5526 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 1.312 inches **Shaft Diameter:** Between 0.2494 inches and 0.2497 inches **Shaft Length:** 0.875 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.734 inches **Shaft Style:** Round **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 348.0 **Maximum Starting Torque:** 1.00 inch-ounces **Maximum Running Torque:** 1.00 inch-ounces

Maximum Stop Torque: 48.00 inch-ounces **Nonturn Device Location:** At 6 oclock **Nonturn Device Radius:** 0.562 inches **Shaft End Play:** 0.007 inches **Shaft Runout:** 0.002 inches **Lateral Runout:** 0.003 inches **Pilot Diameter Runout:** 0.002 inches

NSN 5905-01-036-5526

Precision Wire Wound Variable Resistor - Page 2 of 3



Shaft Radial Play:				
0.004 inches				
Fragility Factor:				
Moderately rugged				
Screw Thread Diameter:				
0.375 inches				
Screw Thread Series Designator:				
Unef				
Screw Thready Qty Per Inch (tpi):				
32.0				
Terminal Location:				
Rear end				
Mounting Method:				
Standard bushing				
Electrical Resistance Per Section:				
5.0 kilohms single section				
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:				
174.0 single section				
Rotary Actuator Travel In Angular Deg:				
360.0				
Function Conformity Tolerance Per Section:				
-0.50/+0.50 single section				
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:				
10F O gingle poetion				
105.0 single section				
Power Dissipation Rating Per Section In Watts:				
-				
Power Dissipation Rating Per Section In Watts:				
Power Dissipation Rating Per Section In Watts: 1.0 free air single section				
Power Dissipation Rating Per Section In Watts: 1.0 free air single section Function Conformity Per Section:				
Power Dissipation Rating Per Section In Watts: 1.0 free air single section Function Conformity Per Section: Single section independent linearity				
Power Dissipation Rating Per Section In Watts: 1.0 free air single section Function Conformity Per Section: Single section independent linearity Fixed Tap Quantity Per Section:				
Power Dissipation Rating Per Section In Watts: 1.0 free air single section Function Conformity Per Section: Single section independent linearity Fixed Tap Quantity Per Section: 1 single section				
Power Dissipation Rating Per Section In Watts: 1.0 free air single section Function Conformity Per Section: Single section independent linearity Fixed Tap Quantity Per Section: 1 single section Tap Location Tolerance Per Section:				
Power Dissipation Rating Per Section In Watts: 1.0 free air single section Function Conformity Per Section: Single section independent linearity Fixed Tap Quantity Per Section: 1 single section Tap Location Tolerance Per Section: -0.5/+0.5 degrees angular rotation single section				
Power Dissipation Rating Per Section In Watts: 1.0 free air single section Function Conformity Per Section: Single section independent linearity Fixed Tap Quantity Per Section: 1 single section Tap Location Tolerance Per Section: -0.5/+0.5 degrees angular rotation single section Resistance Tolerance Per Section In Percent:				
Power Dissipation Rating Per Section In Watts: 1.0 free air single section Function Conformity Per Section: Single section independent linearity Fixed Tap Quantity Per Section: 1 single section Tap Location Tolerance Per Section: -0.5/+0.5 degrees angular rotation single section Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section				
Power Dissipation Rating Per Section In Watts: 1.0 free air single section Function Conformity Per Section: Single section independent linearity Fixed Tap Quantity Per Section: 1 single section Tap Location Tolerance Per Section: -0.5/+0.5 degrees angular rotation single section Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature:				
Power Dissipation Rating Per Section In Watts: 1.0 free air single section Function Conformity Per Section: Single section independent linearity Fixed Tap Quantity Per Section: 1 single section Tap Location Tolerance Per Section: -0.5/+0.5 degrees angular rotation single section Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Continuous motion				
Power Dissipation Rating Per Section In Watts: 1.0 free air single section Function Conformity Per Section: Single section independent linearity Fixed Tap Quantity Per Section: 1 single section Tap Location Tolerance Per Section: -0.5/+0.5 degrees angular rotation single section Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section:				
Power Dissipation Rating Per Section In Watts: 1.0 free air single section Function Conformity Per Section: Single section independent linearity Fixed Tap Quantity Per Section: 1 single section Tap Location Tolerance Per Section: -0.5/+0.5 degrees angular rotation single section Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section: Single section linear				
Power Dissipation Rating Per Section In Watts: 1.0 free air single section Function Conformity Per Section: Single section independent linearity Fixed Tap Quantity Per Section: 1 single section Tap Location Tolerance Per Section: -0.5/+0.5 degrees angular rotation single section Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section: Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:				
Power Dissipation Rating Per Section In Watts: 1.0 free air single section Function Conformity Per Section: Single section independent linearity Fixed Tap Quantity Per Section: 1 single section Tap Location Tolerance Per Section: -0.5/+0.5 degrees angular rotation single section Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section: Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 65.0 single section				
Power Dissipation Rating Per Section In Watts: 1.0 free air single section Function Conformity Per Section: Single section independent linearity Fixed Tap Quantity Per Section: 1 single section Tap Location Tolerance Per Section: -0.5/+0.5 degrees angular rotation single section Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section: Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 65.0 single section Terminal Type And Quantity:				

NSN 5905-01-036-5526

Precision Wire Wound Variable Resistor - Page 3 of 3



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A002a0