## NSN 5905-01-036-6625

Noninductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-036-6625

| Tempurature Coefficient of Resistance in Ppm Per Deg Ceisius:                |
|--|
| -30.0/+30.0  |
| Electrical Resistance:   |
| 80.600 ohms  |
| Resistance Tolerance In Percent:   |
| -1.000/+1.000  |
| Heat Sink Material:  |
| Aluminum alloy   |
| Heat Sink Length:  |
| 6.000 inches   |
| Heat Sink Width:   |
| 4.000 inches   |
| Heat Sink Height:  |
| 2.000 inches   |
| Heat Sink Thickness:   |
| 0.040 inches   |
| Ambient Tempurature In Deg Celsius At Full Rated Power:                      |
| 25.0   |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:              |
| 275.0  |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius:                 |
| -55.0/+275.0   |
| Inclosure Method:  |
| Encased  |
| Terminal Type:   |
| Tab, solder lug  |
| Reliability Indicator:   |
| Established  |
| Reliability Failure Rate Level In Percent:                                   |
| 0.010  |
| Terminal Length:   |
| 0.266 inches   |
| Body Length:   |
| 0.600 inches   |
| Body Width:  |
| 0.334 inches   |
| Body Height:   |
| 0.320 inches   |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 0.444 inches   |
| Power Dissipation Rating In Watts:   |
| a and the said   |

3.000 free air

## NSN 5905-01-036-6625

Noninductive Wire Wound Fixed Resistor - Page 2 of 2



| Terminal Width:  |
|--|
| 0.085 inches   |
| Mounting Hole Size:  |
| 0.093 inches   |
| Style Designator:  |
| Axial terminal (s)   |
| Test Data Document:  |
| 81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain          |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                            |
| Specification Data:  |
| 81349-mil-r-39009/2 government specification   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| <del>-</del>   |
| Demilitarization:  |
| No   |
| Fiig:  |
| A001a0   |
|  |
|  |