NSN 5905-01-036-7876

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-036-7876 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established **Body Length:** 0.196 inches **Body Width:** 0.594 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 260.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method: Terminal Features Provided:** Grounded contact arm **Rotary Actuator Travel In Angular Deg:** 260.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 100.0 single section **Power Dissipation Rating Per Section In Watts:** 0.25 free air single section **Resistance Tolerance Per Section In Percent:** -20.0/+20.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 55.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5905-01-036-7876

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Fiig:

A002a0