NSN 5905-01-036-8709

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-036-8709 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.532 inches **Body Diameter:** 0.875 inches **Shaft Diameter:** 0.2497 inches **Shaft Length:** 0.812 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 0.720 inches **Overall Diameter:** 1.250 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 0.50 inch-ounces **Maximum Running Torque:** 0.50 inch-ounces **Maximum Stop Torque:** 75.00 inch-ounces **Nonturn Device Location:** At 12 oclock **Nonturn Device Radius:** 0.290 inches **Shaft End Play:** 0.010 inches

Shaft Runout: 0.003 inches

NSN 5905-01-036-8709

Lateral Runout:

Precision Wire Wound Variable Resistor - Page 2 of 3



Lateral Kunout.						
0.005 inches						
Pilot Diameter Runout:						
0.003 inches						
Shaft Radial Play:						
0.003 inches						
Fragility Factor:						
Moderately rugged						
Screw Thread Diameter:						
0.375 inches						
Screw Thread Series Designator:						
Unef						
Screw Thready Qty Per Inch (tpi):						
32.0						
Terminal Location:						
Longitudinally positioned on the circumference						
Mounting Method:						
Standard bushing						
Electrical Resistance Per Section:						
500.0 ohms single section						
Rotary Actuator Travel In Angular Deg:						
3600.0						
Function Conformity Tolerance Per Section:						
-0.25/+0.25 single section						
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:						
125.0 single section						
Power Dissipation Rating Per Section In Watts:						
2.0 free air single section						
Function Conformity Per Section:						
Single section independent linearity						
Resistance Tolerance Per Section In Percent:						
-5.0/+5.0 single section						
Actuator Travel Control Feature:						
Stops						
Function Characteristic Per Section:						
Single section linear						
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:						
-20.0/+20.0 single section						
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:						
70.0 single section						
Terminal Type And Quantity:						
3 tab, solder lug						

N/a

Shelf Life:

NSN 5905-01-036-8709

Precision Wire Wound Variable Resistor - Page 3 of 3



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A002a0