## NSN 5905-01-036-8710



Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5905-01-036-8710 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established **Terminal Length:** 0.188 inches **Body Diameter:** 0.385 inches **Body Length:** 0.250 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 180.0 **Center To Center Distance Between Terminals:** 0.344 inches **Terminal Location:** Rear end **Mounting Method: Terminal Electrical Resistance Per Section:** 5.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 360.0 **Center To Center Distance Between Center Terminal And Outside Terminal:** 0.172 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -100.0/+100.0 single section

**Power Dissipation Rating Per Section In Watts:** 

0.5 free air single section

**Resistance Tolerance Per Section In Percent:** 

-20.0/+20.0 single section

**Actuator Travel Control Feature:** 

Continuous motion

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

**Standard Taper Curve Per Section:** 

A single section

## NSN 5905-01-036-8710

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

A002a0