NSN 5905-01-037-7545

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-037-7545

| Section Quantity: |
|---|
| |
| Body Style: |
| Rectangular |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 0.500 inches |
| Shaft Diameter: |
| 0.070 inches |
| Shaft Length: |
| 0.040 inches |
| Body Length: |
| 0.312 inches |
| Body Width: |
| 0.312 inches |
| Body Height: |
| 0.175 inches |
| Shaft Style: |
| Round, slotted |
| Actuator Type: |
| Single shaft |
| Maximum Starting Torque: |
| 3.00 inch-ounces |
| Maximum Running Torque: |
| 3.00 inch-ounces |
| Center To Center Distance Between Terminals: |
| 0.200 inches |
| Terminal Location: |
| Lower adjacent side two rows |
| Mounting Method: |
| Terminal |
| Center To Center Distance Between Terminal Rows: |
| 0.100 inches |
| Features Provided: |
| Humidity proof |
| Electrical Resistance Per Section: |
| 200.000 ohms single section |
| Rotary Actuator Travel In Angular Deg: |
| Between 5040.0 and 5760.0 |
| Center To Center Distance Between Center Terminal And Outside Terminal: |
| 0.100 inches |

NSN 5905-01-037-7545

No Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -70.0/+70.0 single section **Power Dissipation Rating Per Section In Watts:** 0.6 free air single section **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Actuator Travel Control Feature:** Stops and clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 pin Shelf Life: N/a **Unit Of Measure: Demilitarization:**