Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-037-8128

## Section Quantity:

1

Body Style:

Cylindrical

**Reliability Indicator:** 

Not established

#### **Terminal Length:**

0.188 inches

**Body Diameter:** 

0.385 inches

**Body Length:** 

0.250 inches

#### Actuator Type:

Integral knob

#### Effective Electrical Rotation In Deg Angular Rotation:

180.0

### Center To Center Distance Between Terminals:

0.344 inches

**Terminal Location:** 

Rear end

#### **Mounting Method:**

Terminal

#### **Electrical Resistance Per Section:**

100.0 kilohms single section

#### **Rotary Actuator Travel In Angular Deg:**

360.0

#### Center To Center Distance Between Center Terminal And Outside Terminal:

0.172 inches

#### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

### Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

### Power Dissipation Rating Per Section In Watts:

0.5 free air single section

### **Resistance Tolerance Per Section In Percent:**

-20.0/+20.0 single section

### Actuator Travel Control Feature:

Stops

### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

# Standard Taper Curve Per Section:

A single section



Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0