

View Online at <https://aerobasegroup.com/nsn/5905-01-037-8131>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

0.922 inches

Body Diameter:

0.688 inches

Shaft Diameter:

0.125 inches

Shaft Length:

0.125 inches

Mounting Bushing Length:

0.375 inches

Body Length:

0.422 inches

Overall Diameter:

0.907 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

300.0

Maximum Starting Torque:

6.00 inch-ounces

Nonturn Device Location:

At 9 oclock

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Cubic Measure:

0.157 cubic inches

Electrical Resistance Per Section:

1.0 megohms single section

Rotary Actuator Travel In Angular Deg:

300.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Precious Material And Location:

Terminal surfaces gold

Precious Material:

Gold

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0