Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-038-0659

## Section Quantity:

1

Body Style:

Rectangular w/mounting holes

## **Reliability Indicator:**

Not established

### Mounting Hole Diameter:

0.093 inches

#### Shaft Diameter:

0.078 inches

- Shaft Length:
- 0.187 inches

Body Length:

#### 0.500 inches

Body Width:

#### 0.192 inches

**Body Height:** 

0.500 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

#### Effective Electrical Rotation In Deg Angular Rotation:

8640.0

## Lateral Distance Between Mounting Hole Centers:

0.523 inches

**Mounting Facility Quantity:** 

2

Terminal Location:

Rear end

#### **Mounting Method:**

Unthreaded hole

#### **Electrical Resistance Per Section:**

100.0 kilohms single section

#### Rotary Actuator Travel In Angular Deg:

8640.0

### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

# Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-400.0/+400.0 single section

# Power Dissipation Rating Per Section In Watts:

0.75 free air single section



**Resistance Tolerance Per Section In Percent:** 

-5.0/+5.0 single section

## Actuator Travel Control Feature:

Clutch and stops

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

**Terminal Type And Quantity:** 

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0