## NSN 5905-01-038-1107

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-038-1107 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.75000 inches Pilot Length: 0.06200 inches **Undercut Diameter:** 0.781 inches **Undercut Width:** 0.05700 inches **Body Diameter:** 0.875 inches **Shaft Diameter:** 0.1248 inches **Shaft Length:** 0.625 inches **Body Length:** 0.790 inches **Mounting Lip Diameter:** 0.87500 inches **Mounting Lip Depth:** 0.06200 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 340.0 **Maximum Starting Torque:** 0.50 inch-ounces

**Maximum Running Torque:** 0.40 inch-ounces **Shaft End Play:** 0.00500 inches **Shaft Runout:** 0.002 inches

## NSN 5905-01-038-1107

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 3



Lateral Runout:	
0.002 inches	
Pilot Diameter Runout:	
0.00100 inches	
Shaft Radial Play:	
0.001 inches	
Mechanical Backlash In Deg Angular Rotation:	
1.0	
Terminal Location:	
Radially positioned over less than half the circumference	
Mounting Method:	
Clamp ring	
Features Provided:	
Humidity proof	
Electrical Resistance Per Section:	
10.0 kilohms single section	
Rotary Actuator Travel In Angular Deg:	
360.0	
Resistance Tempurature Characteristic Range Per Section In Percent:	
5.0/+5.0 -65 degrees celsius single section and -4.0/+4.0 -15 degrees celsius single section and -5.0/+5.0 105 degrees celsius single	
section and -5.0/+5.0 125 degrees celsius single section	
Function Conformity Tolerance Per Section:	
0.50/+0.50 single section	
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:	
125.0 single section	
Power Dissipation Rating Per Section In Watts:	
1.0 free air single section	
Function Conformity Per Section:	
Single section independent linearity	
Resistance Tolerance Per Section In Percent:	
10.0/+10.0 single section	
Actuator Travel Control Feature:	
Continuous motion	
Function Characteristic Per Section:	
Single section linear	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
70.0 single section	
Terminal Type And Quantity:	
3 turret	
Shelf Life:	
N/a	
Unit Of Measure:	
-	

No

Demilitarization:

## NSN 5905-01-038-1107

Nonprecision Nonwire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0