Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-038-1108

| Section | Quantity: |  |
|---------|-----------|--|

1

Body Style:

Rectangular

**Reliability Indicator:** 

Not established

**Terminal Length:** 

0.188 inches

**Body Length:** 

0.188 inches

**Body Width:** 

0.375 inches

**Body Height:** 

0.375 inches

Actuator Type:

## Flush drive with slot-hole

Effective Electrical Rotation In Deg Angular Rotation:

360.0

**Center To Center Distance Between Terminals:** 

0.300 inches

**Terminal Location:** 

Lower adjacent side single row

#### Mounting Method:

Terminal

**Electrical Resistance Per Section:** 

200.0 ohms single section

**Rotary Actuator Travel In Angular Deg:** 

360.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.150 inches

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

## Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

## **Power Dissipation Rating Per Section In Watts:**

0.5 free air single section

## **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

# **Actuator Travel Control Feature:**

Continuous motion

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

AeroBase Group

Standard Taper Curve Per Section:

A single section

# Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0