Nonprecision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-039-0377

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

## **Overall Length:**

1.500 inches

### **Body Diameter:**

1.156 inches

## Shaft Diameter:

0.250 inches

## Shaft Length:

0.500 inches

## Mounting Bushing Length:

# 0.375 inches

**Body Length:** 

0.812 inches

## **Overall Diameter:**

1.484 inches

### Shaft Style:

Round

### Switch Type:

Rotary

# Switch Voltage Rating In Volts:

125.0

## Actuator Type:

Single shaft

# Effective Electrical Rotation In Deg Angular Rotation:

333.0

### Maximum Starting Torque:

6.00 inch-ounces

### Maximum Running Torque:

1.00 inch-ounces

### Maximum Stop Torque:

192.00 inch-ounces

## Nonturn Device Location:

At 9 oclock

## Nonturn Device Radius:

0.531 inches

# Mechanical Backlash In Deg Angular Rotation:

3.0



**Switch Operating Position:** Start of rotation Switch Contact Arrangement: Single pole, single throw, normally open, both positions maintained **Screw Thread Diameter:** 0.250 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Rear-bottom **Mounting Method:** Standard bushing **Features Provided:** Switch **Electrical Resistance Per Section:** 500.000 ohms single section **Rotary Actuator Travel In Angular Deg:** 333.0 **Resistance Tempurature Characteristic Range Per Section In Percent:** +0.0/+4.5 -55 degrees celsius single section and +0.0/+2.5 -25 degrees celsius single section and +0.0/+1.5 0 degrees celsius single section and -1.5/+1.5 85 degrees celsius single section and +0.0/+3.5 120 degrees celsius single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 120.0 single section **Power Dissipation Rating Per Section In Watts:** 2.25 free air single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Switch Current Type And Rating In Amps: 2.000 ac **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 5 tab, solder lug Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No

# NSN 5905-01-039-0377

Nonprecision Nonwire Wound Variable Resistor - Page 3 of 3

**Fiig:** A002a0

