NSN 5905-01-040-0396

Precision Wire Wound Variable Resistor - Page 1 of 3



o
View Online at https://aerobasegroup.com/nsn/5905-01-040-0396
Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
1.332 inches
Body Diameter:
0.500 inches
Shaft Diameter:
Between 0.1245 inches and 0.1248 inches
Shaft Length:
0.875 inches
Mounting Bushing Length:
0.312 inches
Body Length:
0.305 inches
Overall Diameter:
0.500 inches
Shaft Style:
Round, slotted
Shaft Bearing Type:
Sleeve
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
320.0
Maximum Starting Torque:
12.00 inch-ounces
Maximum Running Torque:
0.20 inch-ounces
Maximum Stop Torque:
80.00 inch-ounces
Nonturn Device Location:
At 6 oclock
Nonturn Device Radius:
0.187 inches
Shaft End Play:
0.006 inches

Shaft Runout: 0.002 inches

NSN 5905-01-040-0396

Lateral Runout:

Gold

Precision Wire Wound Variable Resistor - Page 2 of 3



0.003 inches
Pilot Diameter Runout:
0.002 inches
Shaft Radial Play:
0.003 inches
Fragility Factor:
Moderately rugged
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear end
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
50.0 ohms c and better flooring
Rotary Actuator Travel In Angular Deg:
330.0
Function Conformity Tolerance Per Section:
-1.00/+1.00 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 7th secondary quality
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
7 oclock all primaries
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Precious Material And Location:
Terminals gold
Precious Material:

NSN 5905-01-040-0396

Precision Wire Wound Variable Resistor - Page 3 of 3



Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0