

View Online at <https://aerobasegroup.com/nsn/5905-01-040-1724>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

1.156 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.500 inches

Mounting Bushing Length:

0.375 inches

Body Length:

0.812 inches

Shaft Style:

Round, slotted

Shaft Bearing Type:

Sleeve

Switch Type:

Rotary

Switch Voltage Rating In Volts:

125.0

Contact Arm Electrical Off Position:

Fully cw

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

292.0

Maximum Starting Torque:

6.00 inch-ounces

Maximum Running Torque:

6.00 inch-ounces

Maximum Stop Torque:

192.00 inch-ounces

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.531 inches

Mechanical Backlash In Deg Angular Rotation:

1.5

Switch Operating Position:

Start of rotation

Switch Contact Arrangement:

Single pole, single throw, normally open, both positions maintained

Fragility Factor:

Moderately rugged

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Rear-bottom

Mounting Method:

Standard bushing

Features Provided:

Switch

Electrical Resistance Per Section:

1.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

333.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

Power Dissipation Rating Per Section In Watts:

2.25 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Switch Current Type And Rating In Amps:

2.000 ac

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0