## NSN 5905-01-040-2672

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-040-2672 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.475 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 1.000 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.672 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 295.0 **Nonturn Device Location:** At 3 oclock and at 9 oclock **Nonturn Device Radius:** 0.500 inches **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Rear end **Mounting Method:** Standard bushing **Features Provided:** Shaft seal **Electrical Resistance Per Section:** 75.0 ohms single section

Rotary Actuator Travel In Angular Deg: 295.0

## NSN 5905-01-040-2672

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 120.0 single section **Power Dissipation Rating Per Section In Watts:** 0.5 free air single section **Resistance Tolerance Per Section In Percent:** -25.0/+25.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a **Unit Of Measure: Demilitarization:** No