NSN 5905-01-040-4003

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-040-4003

Section Quantity:
3
Body Style:
Cylindrical servo mounted
Reliability Indicator:
Not established
Pilot Diameter:
Between 0.3745 inches and 0.3750 inches
Pilot Length:
0.0400 inches
Undercut Diameter:
0.440 inches
Undercut Width:
0.0570 inches
Body Diameter:
0.510 inches
Shaft Diameter:
0.124 inches
Shaft Length:
Between 0.280 inches and 0.320 inches
Body Length:
Between 0.280 inches and 0.320 inches
Mounting Lip Diameter:
Between 0.4970 inches and 0.5000 inches
Mounting Lip Depth:
0.0620 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
5.0 kilohms single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section

-5.0/+5.0 single section

Resistance Tolerance Per Section In Percent:

NSN 5905-01-040-4003

Precision Wire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
3 clamp
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0