

View Online at <https://aerobasegroup.com/nsn/5905-01-040-4007>

**Section Quantity:**

1

**Body Style:**

Cylindrical tab/flange mounted

**Reliability Indicator:**

Not established

**Body Diameter:**

0.750 inches

**Mounting Hole Diameter:**

0.130 inches

**Body Length:**

0.375 inches

**Actuator Type:**

Flush drive with slot-hole

**Effective Electrical Rotation In Deg Angular Rotation:**

220.0

**Fragility Factor:**

Moderately delicate

**Lateral Distance Between Mounting Hole Centers:**

1.000 inches

**Mounting Facility Quantity:**

2

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Unthreaded hole

**Features Provided:**

Grounded contact arm

**Electrical Resistance Per Section:**

15.0 ohms single section

**Rotary Actuator Travel In Angular Deg:**

360.0

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

105.0 single section

**Power Dissipation Rating Per Section In Watts:**

2.0 free air single section

**Resistance Tolerance Per Section In Percent:**

-20.0/+20.0 single section

**Actuator Travel Control Feature:**

Continuous motion

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

40.0 single section

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0