

View Online at <https://aerobasegroup.com/nsn/5905-01-040-4636>

**Section Quantity:**

1

**Body Style:**

Rectangular

**Reliability Indicator:**

Not established

**Terminal Length:**

0.200 inches

**Body Length:**

0.375 inches

**Body Width:**

0.190 inches

**Body Height:**

0.375 inches

**Actuator Type:**

Flush drive with slot-hole

**Effective Electrical Rotation In Deg Angular Rotation:**

280.0

**Maximum Starting Torque:**

5.00 inch-ounces

**Maximum Running Torque:**

5.00 inch-ounces

**Center To Center Distance Between Terminals:**

0.200 inches

**Terminal Location:**

Lower adjacent side two rows

**Mounting Method:**

Terminal

**Center To Center Distance Between Terminal Rows:**

0.100 inches

**Features Provided:**

Humidity proof

**Electrical Resistance Per Section:**

10.000 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

280.0

**Center To Center Distance Between Center Terminal And Outside Terminal:**

0.100 inches

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

125.0 single section

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-100.0/+100.0 single section

**Power Dissipation Rating Per Section In Watts:**

0.5 free air single section

**Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

**Actuator Travel Control Feature:**

Stops

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

85.0 single section

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

3 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0