NSN 5905-01-040-7417

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-040-7417 **Section Quantity: Body Style:** Rectangular **Reliability Indicator:** Not established **Body Length:** 0.344 inches **Body Width:** 0.312 inches **Body Height:** 0.355 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 240.0 **Terminal Location:** Lower adjacent side single row **Mounting Method: Terminal Electrical Resistance Per Section:** 200.0 ohms single section **Rotary Actuator Travel In Angular Deg:** 280.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -250.0/+250.0 single section **Power Dissipation Rating Per Section In Watts:** 0.5 free air single section **Resistance Tolerance Per Section In Percent:** -20.0/+20.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 wire lead Shelf Life:

N/a

NSN 5905-01-040-7417

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



		• -		
	In	11	<i>(</i>)+	Measure:
v	,,,		U I	wicasui c.

--

Demilitarization:

No

Fiig:

A002a0