NSN 5905-01-041-2654

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-041-2654 **Section Quantity:** 2 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.907 inches **Body Diameter:** 1.156 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.625 inches **Mounting Bushing Length:** 0.500 inches **Body Length:** 1.266 inches **Overall Diameter:** 1.453 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 312.0 **Nonturn Device Location:** At 9 oclock Radially positioned over less than half the circumference

Nonturn Device Radius: 0.531 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location: Mounting Method:** Locking bushing **Features Provided:** Shaft locking device

NSN 5905-01-041-2654

Precision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:	
250.000 kilohms all sections	
Rotary Actuator Travel In Angular Deg:	
312.0	
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:	
120.0 all sections	
Power Dissipation Rating Per Section In Watts:	
2.25 7th secondary finish	
Resistance Tolerance Per Section In Percent:	
-10.0/+10.0 all sections	
Actuator Travel Control Feature:	
Stops	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
70.0 all sections	
Terminal Type And Quantity:	
6 tab, solder lug	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A002a0	