## NSN 5905-01-041-7884

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-041-7884 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.3750 inches Pilot Length: 0.0620 inches **Overall Length:** 1.500 inches **Undercut Diameter:** 0.375 inches **Undercut Width:** 0.0620 inches **Body Diameter:** 0.531 centimeters **Shaft Diameter:** 0.0935 inches **Shaft Length:** 0.250 inches **Body Length:** 1.125 inches **Overall Diameter:** 0.531 inches **Mounting Lip Diameter:** 0.5310 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Effective Electrical Rotation In Deg Angular Rotation:** 

**Actuator Type:** Single shaft 3600.0 **Maximum Starting Torque:** 0.15 inch-ounces **Maximum Running Torque:** 0.15 inch-ounces

## NSN 5905-01-041-7884

Precision Wire Wound Variable Resistor - Page 2 of 3



Maximum Stop Torque:
20.00 inch-ounces
Shaft End Play:
0.005 inches
Shaft Runout:
0.001 inches
Lateral Runout:
0.001 inches
Pilot Diameter Runout:
0.001 inches
Shaft Radial Play:
0.001 inches
Fragility Factor:
Moderately rugged
Terminal Location:
Rear end
Mounting Method:
Clamp ring
Features Provided:
Humidity proof
Cubic Measure:
0.249 cubic inches
Electrical Resistance Per Section:
5.0 percent, rated amperes c and better flooring
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.10/+0.10 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
2.5 7th secondary quality
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
7 oclock all primaries
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

-20.0/+20.0 single section

## NSN 5905-01-041-7884

Precision Wire Wound Variable Resistor - Page 3 of 3



Precious Material And Location:
Terminal surfaces gold
Precious Material And Weight:
0.120 gold grains, troy
Precious Material:
Gold
Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0