## NSN 5905-01-042-2344

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-042-2344 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.656 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 1.098 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 2.130 inches **Shaft Style:** Round Switch Type: Push **Actuator Type:** Single shaft **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.229 inches **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over more than half the circumference **Mounting Method:** Standard bushing **Features Provided:** Switch **Terminal Type And Quantity:** 

11 tab, solder lug Shelf Life:

N/a

## NSN 5905-01-042-2344

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A002a0