Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-042-2350

### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

### **Reliability Indicator:**

Not established

#### **Body Diameter:**

0.500 inches

#### Shaft Diameter:

0.125 inches

#### Shaft Length:

0.875 inches

#### Mounting Bushing Length:

0.250 inches

#### Body Length:

### 0.531 inches

Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

### Nonturn Device Location:

At 4'30 oclock and at 10'30 oclock

#### Nonturn Device Radius:

0.245 inches

#### Screw Thread Diameter:

0.250 inches

### Screw Thread Series Designator:

Unef

### Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Rear end

# **Mounting Method:**

Standard bushing

# Features Provided:

Panel seal and shaft seal

# **Electrical Resistance Per Section:**

100.0 ohms single section

# Rotary Actuator Travel In Angular Deg:

Between 292.0 and 298.0

# Resistance Tempurature Characteristic Range Per Section In Percent:

-3.0/+0.0 -55 degrees celsius single section and -5.0/+10.0 -25 degrees celsius single section and -5.0/+10.0 25 degrees celsius single section and +0.0/+3.0 120 degrees celsius single section



# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

# Power Dissipation Rating Per Section In Watts:

0.25 free air single section

**Resistance Tolerance Per Section In Percent:** 

-10.0/+10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

C single section

# Test Data Document:

81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Terminal Type And Quantity:**

3 tab, solder lug

#### **Specification Data:**

81349-mil-r-94/3 government specification

Shelf Life:

N/a

Unit Of Measure:

--

### Demilitarization:

No

Fiig:

A002a0