## NSN 5905-01-042-3743

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-042-3743 **Section Quantity: Body Style:** Rectangular **Reliability Indicator:** Not established **Terminal Length:** 0.187 inches **Body Length:** 0.315 inches **Body Width:** 0.312 inches **Body Height:** 0.375 inches **Actuator Type:** Flush drive with slot-hole **Center To Center Distance Between Terminals:** 0.100 inches **Terminal Location:** Lower adjacent side two rows **Mounting Method: Terminal Center To Center Distance Between Terminal Rows:** 0.100 inches **Electrical Resistance Per Section:** 2.0 kilohms single section **Center To Center Distance Between Center Terminal And Outside Terminal:** 0.141 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -100.0/+100.0 single section **Power Dissipation Rating Per Section In Watts:** 0.5 free air single section **Resistance Tolerance Per Section In Percent:** 

-10.0/+10.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

**Terminal Type And Quantity:** 

3 pin

Shelf Life:

N/a

## NSN 5905-01-042-3743

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A002a0