## NSN 5905-01-042-7500

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-042-7500 **Section Quantity: Body Style:** Rectangular **Reliability Indicator:** Established **Reliability Failure Rate Level In Percent:** 0.010 **Overall Length:** 0.800 inches **Terminal Length:** 0.300 inches **Overall Height:** 0.375 inches **Overall Width:** 0.170 inches **Shaft Diameter:** 0.075 inches **Shaft Length:** 0.080 inches **Body Length:** 0.420 inches **Body Width:** 0.170 inches **Body Height:** 0.375 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** Between 5400.0 and 10800.0 **Maximum Starting Torque:** 5.00 inch-ounces **Maximum Running Torque:** 

5.00 inch-ounces

Center To Center Distance Between Terminals:
0.200 inches

Fragility Factor:

Moderately rugged

## NSN 5905-01-042-7500

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



## **End Application:**

Countermeasure set, an/slq-32, communications, lha; sonar signal proceesing sys, an/sqq-2 (v); radio terminal set, an/srq-4; tactical air opns module (an/tyq-(23), aircraft, ac-130h, mc-130h, ec-130e, hc-130; strategic weapon systems (poseidon and trident) torpedo, mk 48; missile, all-weather anti-ship, harpoon (agm-84); communications systems an/wsc-3

<b>T</b> -			_ocati	!
10	rmin	21 I	OC 21	nn:

Rear end

**Mounting Method:** 

Terminal

**Cubic Measure:** 

0.051 cubic inches

**Electrical Resistance Per Section:** 

5.000 percent, rated amperes c and better flooring

**Center To Center Distance Between Center Terminal And Outside Terminal:** 

0.100 inches

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0/+50.0 single section

**Power Dissipation Rating Per Section In Watts:** 

0.75 7th secondary quality

**Resistance Tolerance Per Section In Percent:** 

-5.0/+5.0 single section

**Actuator Travel Control Feature:** 

Clutch

**Criticality Code Justification:** 

Feat

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

**Standard Taper Curve Per Section:** 

A single section

**Special Features:** 

Weapon system essential

**Test Data Document:** 

81349-mil-r-39015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

3 pin

**Specification Data:** 

81349-mil-r-39015/3 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:**