## NSN 5905-01-043-0432

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-043-0432

-400.0/+400.0 Electrical Resistance: 1.000 ohms Resistance Tolorance in Percent: -5.000/+5.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Terminal Length: 1.375 inches Body Diameter: 0.187 inches Body Length: 0.500 inches Power Dissipation Rating in Watts: 2.500 free air Style Designator: Axial terminal each end Test Data Document: B1494-mili-28-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Sheff Life: N/a Unit Of Measure:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance in Percent: -5.0004-5.000 Ambient Tempurature in Deg Celsius At Full Rated Power: -25.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: -275.0 Ambient Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.04-275.0 Inclosure Method:	-400.0/+400.0
Resistance Tolerance in Percent: -5.000/45.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.04/275.0 Itempurature Method: Encapsulated Terminal Type: Wire lead Terminal Length: 1.375 inches Body Diameter: 0.187 inches Body Length: 0.500 inches Power Dissipation Rating in Watts: 2.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-mill-r26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format: excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.) Shelf Life: Na Unit Of Measure: - Demilitarization: No Filg:	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Terminal Length: 1.375 inches Body Diameter: 0.187 inches Body Length: 0.550 inches Power Dissipation Rating In Watts: 2.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-milt-26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: N/a Unit Of Measure: - Demilitarization: No Flig:	1.000 ohms
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  25.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -55.0/+275.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Terminal Length:  1.375 inches  Body Diameter:  0.187 inches  Body Length:  0.500 inches  Power Dissipation Rating In Watts:  2.500 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-mili-r-26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Flig:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Terminal Length: 1.375 inches Body Diameter: 0.187 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 2.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-milt-r-26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: - Demilitarization: No Flig:	-5.000/+5.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0  Inclosure Method: Encapsulated Terminal Type: Wire lead  Terminal Length: -1.375 inches Body Diameter: 0.187 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 2.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-mili-726-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wrire lead Terminal Length: 1.375 inches Body Diameter: 0.187 inches Body Diameter: 0.187 inches Body Dismeter: 0.500 inches Power Dissipation Rating In Watts: 2.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Sheft Life: No Unit Of Measure: Demilitarization: No Fiig:	25.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Terminal Length: 1.375 inches Body Diameter: 0.187 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 2.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-mill-r-26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
Inclosure Method: Encapsulated Terminal Type: Wire lead Terminal Length: 1.375 inches Body Diameter: 0.187 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 2.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	275.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Terminal Length: 1.375 inches Body Diameter: 0.187 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 2.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "*, etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Terminal Length: 1.375 inches Body Diameter: 0.187 inches Body Diameter: 0.187 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 2.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	-55.0/+275.0
Terminal Type:  Wire lead  Terminal Length:  1.375 inches  Body Diameter:  0.187 inches  Body Length:  0.500 inches  Power Dissipation Rating In Watts:  2.500 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-mil-r-26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fig:	Inclosure Method:
Wire lead  Terminal Length:  1.375 inches  Body Diameter:  0.187 inches  Body Length:  0.500 inches  Power Dissipation Rating In Watts:  2.500 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-mil-r-26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fig:	Encapsulated
Terminal Length:  1.375 inches  Body Diameter:  0.187 inches  Body Length:  0.500 inches  Power Dissipation Rating In Watts:  2.500 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-mil-r-26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Terminal Type:
1.375 inches  Body Diameter: 0.187 inches  Body Length: 0.500 inches  Power Dissipation Rating In Watts: 2.500 free air  Style Designator: Axial terminal each end  Test Data Document: 81349-mil-r-26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fig:	Wire lead
Body Diameter:  0.187 inches  Body Length: 0.500 inches  Power Dissipation Rating In Watts: 2.500 free air  Style Designator: Axial terminal each end  Test Data Document: 81349-mil-r-26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fig:	Terminal Length:
0.187 inches  Body Length: 0.500 inches  Power Dissipation Rating In Watts: 2.500 free air  Style Designator: Axial terminal each end  Test Data Document: 81349-mil-r-26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fig:	1.375 inches
Body Length:  0.500 inches  Power Dissipation Rating In Watts: 2.500 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-mil-r-26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Filig:	Body Diameter:
0.500 inches  Power Dissipation Rating In Watts: 2.500 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-mil-r-26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fitig:	0.187 inches
Power Dissipation Rating In Watts:  2.500 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-mil-r-26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Body Length:
2.500 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-mil-r-26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	0.500 inches
Style Designator:  Axial terminal each end  Test Data Document:  81349-mil-r-26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Power Dissipation Rating In Watts:
Axial terminal each end  Test Data Document:  81349-mil-r-26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	2.500 free air
Test Data Document:  81349-mil-r-26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Style Designator:
81349-mil-r-26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Axial terminal each end
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	81349-mil-r-26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
N/a Unit Of Measure: Demilitarization: No Fiig:	environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization:  No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0