Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-043-4288

## Section Quantity:

1

Body Style:

Rectangular w/mounting holes

## **Reliability Indicator:**

Not established

#### Mounting Slot Width:

0.093 inches

#### Shaft Diameter:

0.093 inches

#### Shaft Length:

0.105 inches

#### **Body Length:**

0.500 inches

#### Body Width:

0.190 inches

## Body Height:

0.500 inches

# Shaft Style:

Round, slotted

## Actuator Type:

Single shaft

#### Effective Electrical Rotation In Deg Angular Rotation:

9000.0

#### **Fragility Factor:**

Moderately delicate

#### Lateral Distance Between Mounting Hole Centers:

0.520 inches

#### **Mounting Facility Quantity:**

2

## **Terminal Location:**

Rear end

## **Mounting Method:**

Slot

#### Features Provided:

Humidity proof

#### **Electrical Resistance Per Section:**

25.0 percent, rated amperes c and better flooring

## Rotary Actuator Travel In Angular Deg:

9000.0

#### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section



Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0/+50.0 single section

#### Power Dissipation Rating Per Section In Watts:

1.0 7th secondary quality

**Resistance Tolerance Per Section In Percent:** 

-5.0/+5.0 single section

## **Actuator Travel Control Feature:**

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

**Terminal Type And Quantity:** 

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0