

View Online at <https://aerobasegroup.com/nsn/5905-01-043-4291>

Section Quantity:

2

Body Style:

Rectangular bushing mounted

Reliability Indicator:

Not established

Shaft Diameter:

0.126 inches

Shaft Length:

0.931 inches

Mounting Bushing Length:

0.266 inches

Body Length:

1.094 inches

Body Width:

0.625 inches

Body Height:

0.625 inches

Undercut Diameter:

0.079 inches

Shaft Style:

Round, stepped

Actuator Type:

Dual concentric

Undercut Length:

0.290 inches

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Lower adjacent side single row

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

1.0 kilohms all sections

Resistance Temperature Characteristic Range Per Section In Percent:

+0.0/+5.5 -55 degrees celsius all sections and +0.0/+3.0 -25 degrees celsius all sections and +0.0/+1.5 0 degrees celsius all sections and -2.0/+2.0 85 degrees celsius all sections and +0.0/+4.5 120 degrees celsius all sections

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 all sections

Power Dissipation Rating Per Section In Watts:

0.5 free air all sections

Resistance Tolerance Per Section In Percent:

-20.0/+20.0 all sections

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 all sections

Standard Taper Curve Per Section:

A all sections

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0