## NSN 5905-01-044-1520

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-044-1520

Electrical Resistance: 10.000 kliohms Resistance Tolerance In Percent: 11.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 125.0/175.0 Inclosure Method: 125.0 125.	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Encapsulated Ferminal Type: Write laad Reliability Indicator: Established Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 30dy Diameter: 1.125 inches 30dy Length: 1.375 inches 90wer Dissipation Rating In Watts: 1.25 free air 8tyle Designator: Axial terminal each end Feet Data Document: 31449-milr-55182/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain anvironmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: Via Julit of Measure: - Demilitarization:	-100.0/+100.0
Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Incapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 30dy Diameter: 1.0125 inches Power Dissipation Rating In Watts: 1.125 free air Style Designator: Axial terminal each end Test Data Document: 131349-mil-r-55182/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain service mental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Juit Of Measure: Demilitarization:	510.000 kilohms
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/4175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Body Diameter: 1.035 inches Power Dissipation Rating In Watts: 1.0375 inches Power Dissipation Rating In Watts: 1.0481e Tee air Style Designator: 843el terminal each end Test Data Document: 81349-mili-r-55182/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain sonvironmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Wie Julit Of Measure: 1000 1011 1012 1013 1013 1013 1013 1013	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  175.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/4175.0  Inclosure Method:  Incapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Established  Reliability Failure Rate Level In Percent:  1.000  30dy Diameter:  1.125 inches  30dy Length:  1.375 inches  Power Dissipation Rating in Watts:  1.425 free air  Style Designator:  Avial terminal each end  Test Data Document:  13149-mil-r-55182/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Via  Unit Of Measure:  - Demilitarization:	-1.000/+1.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  175.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+175.0  Tempurature Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Established  Reliability Failure Rate Level In Percent:  1.000  30dy Diameter:  0.125 inches  30dy Length:  0.375 inches  Power Dissipation Rating In Watts:  0.125 free air  Style Designator:  Axial terminal each end  Test Data Document:  31349-mil-r-55182/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "', etc.).  Shelf Life:  V/a  Juit Of Measure:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Prempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+175.0  nclosure Method: Encapsulated Preminal Type:  Mire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000  30dy Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-55182/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain servironmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.).  Shelf Life:  Wa Juit Of Measure: - Demilitarization:	125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+175.0 nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 80dy Diameter: 1.125 inches 80dy Length: 1.0375 inches Power Dissipation Rating In Watts: 1.125 free air Style Designator: 4xial terminal each end Fest Data Document: 181349-mil-r-55182/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.).  Shelf Life:  Wa Unit Of Measure: - Demilitarization:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 30dy Diameter: 0.125 inches 30dy Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Fest Data Document: 31349-milr-55182/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: Wa Juit of Measure:	175.0
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Fest Data Document: 81349-mil-r-55182/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa Juit Of Measure: - Demilitarization:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 3ody Diameter: 0.125 inches 3ody Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Avial terminal each end Fest Data Document: 31349-mil-r-55182/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain servironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: W/a Juit Of Measure:	-55.0/+175.0
Ferminal Type:  Wire lead  Reliability Indicator:  Established  Reliability Failure Rate Level In Percent:  1.000  Rody Diameter:  0.125 inches  Rody Length:  0.375 inches  Power Dissipation Rating In Watts:  0.125 free air  Style Designator:  Axial terminal each end  Fest Data Document:  81349-mil-r-55182/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Wa  Jnit Of Measure:  Demilitarization:	Inclosure Method:
Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Rody Diameter: 0.125 inches Rody Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Fest Data Document: 81349-mil-r-55182/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: W/a Jnit Of Measure: - Demilitarization:	Encapsulated
Reliability Indicator:  Established Reliability Failure Rate Level In Percent:  1.000 Redy Diameter:  0.125 inches Redy Length:  0.375 inches Power Dissipation Rating In Watts:  0.125 free air Style Designator: Avial terminal each end Fest Data Document: 81349-mil-r-55182/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain servironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a Unit Of Measure:  Demilitarization:	Terminal Type:
Established Reliability Failure Rate Level In Percent:  1.000 Rody Diameter:  1.125 inches Rody Length:  1.0375 inches Power Dissipation Rating In Watts:  1.125 free air  Style Designator:  Axial terminal each end Fest Data Document:  1.31349-mil-r-55182/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain servironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	Wire lead
Reliability Failure Rate Level In Percent:  1.000  3.0dy Diameter:  0.125 inches  3.0dy Length:  0.375 inches  2.0ver Dissipation Rating In Watts:  0.125 free air  Style Designator:  Axial terminal each end  7.5st Data Document:  3.1349-mil-r-55182/3 specification (includes engineering type bulletins, brochures, etc, that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain servironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  W/a  Junit Of Measure:  - Demilitarization:	Reliability Indicator:
Body Diameter:  0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Fest Data Document: 31349-mil-r-55182/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: W/a Julit Of Measure: - Demilitarization:	Established
Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Fest Data Document: 81349-mil-r-55182/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: W/a Unit Of Measure:	Reliability Failure Rate Level In Percent:
20.125 inches  Body Length:  20.375 inches  Power Dissipation Rating In Watts:  20.125 free air  Style Designator:  Axial terminal each end  Fest Data Document:  21.349-mil-r-55182/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Wa  Unit Of Measure:  Demilitarization:	1.000
Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Fest Data Document: 81349-mil-r-55182/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life:  Wa Unit Of Measure: Demilitarization:	Body Diameter:
D.375 inches  Power Dissipation Rating In Watts: D.125 free air  Style Designator: Axial terminal each end  Fest Data Document: B1349-mil-r-55182/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	0.125 inches
Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Fest Data Document: 31349-mil-r-55182/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Jnit Of Measure:	Body Length:
O.125 free air  Style Designator:  Axial terminal each end  Fest Data Document:  81349-mil-r-55182/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	0.375 inches
Axial terminal each end  Test Data Document:  31349-mil-r-55182/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	Power Dissipation Rating In Watts:
Axial terminal each end  Fest Data Document:  81349-mil-r-55182/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  V/a  Unit Of Measure:  Demilitarization:	0.125 free air
Test Data Document:  31349-mil-r-55182/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	Style Designator:
31349-mil-r-55182/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Jnit Of Measure:  Demilitarization:	Axial terminal each end
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Jnit Of Measure:  Demilitarization:	Test Data Document:
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Jnit Of Measure:  Complete the conditions that are shown as "typical", "average", "", etc.).  Demilitarization:	81349-mil-r-55182/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
Shelf Life: N/a Unit Of Measure: Demilitarization:	format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
N/a Unit Of Measure: Demilitarization:	environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Jnit Of Measure: - Demilitarization:	Shelf Life:
- Demilitarization:	N/a
	Unit Of Measure:
No	Demilitarization:
	No
Filg:	Fiig:
4001a0	A001a0