## NSN 5905-01-044-4407

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-044-4407 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.875 inches **Shaft Diameter:** 0.2497 inches **Shaft Length:** 0.812 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 0.720 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 1080.0 **Maximum Starting Torque:** 0.50 inch-ounces **Maximum Running Torque:** 0.50 inch-ounces **Maximum Stop Torque:** 75.00 inch-ounces **Nonturn Device Location:** At 12 oclock **Nonturn Device Radius:** 0.290 inches **Shaft End Play:** 0.010 inches

Shaft Runout:
0.003 inches
Lateral Runout:
0.005 inches
Pilot Diameter Runout:
0.003 inches

## NSN 5905-01-044-4407

Precision Wire Wound Variable Resistor - Page 2 of 3



Shaft Radial Play:						
0.003 inches						
Fragility Factor:						
Moderately rugged						
Screw Thread Diameter:						
0.375 inches						
Screw Thread Series Designator:						
Unef						
Screw Thready Qty Per Inch (tpi):						
32.0						
Terminal Location:						
Radially positioned over less than half the circumference						
Mounting Method:						
Standard bushing						
Electrical Resistance Per Section:						
10.0 kilohms single section						
Rotary Actuator Travel In Angular Deg:						
1080.0						
Function Conformity Tolerance Per Section:						
-0.25/+0.25 single section						
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:						
125.0 single section						
Power Dissipation Rating Per Section In Watts:						
1.0 free air single section						
Function Conformity Per Section:						
Single section independent linearity						
Resistance Tolerance Per Section In Percent:						
-5.0/+5.0 single section						
Actuator Travel Control Feature:						
Stops						
Function Characteristic Per Section:						
Single section linear						
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:						
-20.0/+20.0 single section						
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:						
70.0 single section						
Precious Material And Location:						
Terminals gold						
Precious Material:						
Gold						
Terminal Type And Quantity:						
3 tab, solder lug						
Shelf Life:						
N/a						

N/a

## NSN 5905-01-044-4407

Precision Wire Wound Variable Resistor - Page 3 of 3



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A002a0