## NSN 5905-01-044-7443

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-044-7443 **Section Quantity: Body Style:** Cylindrical **Body Diameter:** 0.270 inches **Body Length:** 0.215 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 215.0 **Maximum Starting Torque:** 5.00 inch-ounces **Maximum Running Torque:** 5.00 inch-ounces **Terminal Location:** Rear end **Mounting Method: Terminal Electrical Resistance Per Section:** 1.000 kilohms single section **Rotary Actuator Travel In Angular Deg:** 240.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -100.0/+100.0 single section **Power Dissipation Rating Per Section In Watts:** 0.5 free air single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** 

A single section

**Terminal Type And Quantity:** 

3 wire lead

## NSN 5905-01-044-7443

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0