Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-044-8470

### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

#### **Overall Length:**

1.250 inches

#### Body Diameter:

1.156 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

0.625 inches

#### Mounting Bushing Length:

# 0.375 inches

**Body Length:** 

0.656 inches

#### **Overall Diameter:**

1.750 inches

## Shaft Style:

Round, slotted

## Shaft Bearing Type:

Sleeve

#### Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

292.0

## Maximum Starting Torque:

6.00 inch-ounces

#### Maximum Running Torque:

6.00 inch-ounces

#### Maximum Stop Torque:

192.00 inch-ounces

## Nonturn Device Location:

At 9 oclock

## Nonturn Device Radius:

0.531 inches

## Screw Thread Diameter:

0.375 inches

## Screw Thread Series Designator:

Unef

# NSN 5905-01-044-8470

---

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 50.0 kilohms all sections **Rotary Actuator Travel In Angular Deg:** 312.0 **Resistance Tempurature Characteristic Range Per Section In Percent:** +0.0/+7.0 -55 degrees celsius single section and +0.0/+3.5 -25 degrees celsius single section and +0.0/+2.0 0 degrees celsius single section and +0.0/+2.5 85 degrees celsius single section and +0.0/+5.5 120 degrees celsius single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 120.0 single section **Power Dissipation Rating Per Section In Watts:** 2.25 free air single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A002a0