Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-044-9536

# Section Quantity:

1

Body Style:

Rectangular bushing mounted

# Reliability Indicator:

Not established

### Shaft Diameter:

0.115 inches

#### Shaft Length:

3.312 inches

### Mounting Bushing Length:

0.250 inches

#### Body Length:

1.312 inches

#### Body Width:

0.190 inches

## **Body Height:**

0.320 inches

# Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

7920.0

## Fragility Factor:

Moderately delicate

#### Screw Thread Diameter:

0.190 inches

## Screw Thread Series Designator:

Unf

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Rear end

# Mounting Method:

Standard bushing

# **Features Provided:**

Humidity proof

# **Electrical Resistance Per Section:**

50.0 ohms single section

# Rotary Actuator Travel In Angular Deg:

7920.0



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 175.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -50.0/+50.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 wire lead Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A002a0