NSN 5905-01-044-9537

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-044-9537

view Offilite at https://aerobasegroup.com/hist//0000-01-044-000/
Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
0.500 inches
Shaft Diameter:
0.125 inches
Shaft Length:
1.000 inches
Mounting Bushing Length:
0.500 inches
Body Length:
0.469 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
295.0
295.0
295.0 Nonturn Device Location:
295.0 Nonturn Device Location: At 4'30 oclock and at 10'30 oclock
295.0 Nonturn Device Location: At 4'30 oclock and at 10'30 oclock Nonturn Device Radius:
295.0 Nonturn Device Location: At 4'30 oclock and at 10'30 oclock Nonturn Device Radius: 0.245 inches
295.0 Nonturn Device Location: At 4'30 oclock and at 10'30 oclock Nonturn Device Radius: 0.245 inches Screw Thread Diameter:
295.0 Nonturn Device Location: At 4'30 oclock and at 10'30 oclock Nonturn Device Radius: 0.245 inches Screw Thread Diameter: 0.250 inches
295.0 Nonturn Device Location: At 4'30 oclock and at 10'30 oclock Nonturn Device Radius: 0.245 inches Screw Thread Diameter: 0.250 inches Screw Thread Series Designator:
295.0 Nonturn Device Location: At 4'30 oclock and at 10'30 oclock Nonturn Device Radius: 0.245 inches Screw Thread Diameter: 0.250 inches Screw Thread Series Designator: Unef
Nonturn Device Location: At 4'30 oclock and at 10'30 oclock Nonturn Device Radius: 0.245 inches Screw Thread Diameter: 0.250 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi):
Nonturn Device Location: At 4'30 oclock and at 10'30 oclock Nonturn Device Radius: 0.245 inches Screw Thread Diameter: 0.250 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0
Nonturn Device Location: At 4'30 oclock and at 10'30 oclock Nonturn Device Radius: 0.245 inches Screw Thread Diameter: 0.250 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location:
Nonturn Device Location: At 4'30 oclock and at 10'30 oclock Nonturn Device Radius: 0.245 inches Screw Thread Diameter: 0.250 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Rear end
Nonturn Device Location: At 4'30 oclock and at 10'30 oclock Nonturn Device Radius: 0.245 inches Screw Thread Diameter: 0.250 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Rear end Mounting Method:
Nonturn Device Location: At 4'30 oclock and at 10'30 oclock Nonturn Device Radius: 0.245 inches Screw Thread Diameter: 0.250 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Rear end Mounting Method: Standard bushing
Nonturn Device Location: At 4'30 oclock and at 10'30 oclock Nonturn Device Radius: 0.245 inches Screw Thread Diameter: 0.250 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Rear end Mounting Method: Standard bushing Electrical Resistance Per Section:
Nonturn Device Location: At 4'30 oclock and at 10'30 oclock Nonturn Device Radius: 0.245 inches Screw Thread Diameter: 0.250 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Rear end Mounting Method: Standard bushing Electrical Resistance Per Section: 2.5 kilohms single section

175.0 single section

NSN 5905-01-044-9537

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Tempurature Coefficient	Of Resistance I	Per Section In	Ppm Per Deg Celsius:
-------------------------	-----------------	----------------	----------------------

-150.0/+150.0 single section

Power Dissipation Rating Per Section In Watts:

0.5 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

125.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0