Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-045-5286

view Online at https://aerobasegroup.com/nsn/5905-01-045-5286
Section Quantity:
1
Body Style:
Rectangular
Terminal Length:
0.172 inches
Shaft Diameter:
Between 0.070 inches and 0.080 inches
Shaft Length:
Between 0.030 inches and 0.050 inches
Body Length:
Between 0.520 inches and 0.560 inches
Body Width:
Between 0.090 inches and 0.110 inches
Body Height:
Between 0.140 inches and 0.160 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Maximum Starting Torque:
2.00 inch-ounces
Maximum Running Torque:
2.00 inch-ounces
Center To Center Distance Between Terminals:
Between 0.390 inches and 0.410 inches
Terminal Location:
Lower adjacent side single row
Mounting Method:
Terminal
Electrical Resistance Per Section:
100.000 kilohms single section
Center To Center Distance Between Center Terminal And Outside Terminal:
Between 0.090 inches and 0.110 inches
Resistance Tolerance Per Section In Percent:
-2.0/+2.0 single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:

--

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A002a0