## NSN 5905-01-045-7552

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-045-7552

-100.0/+100.0 Electrical Resistance: 4.750 kilohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Eull Rated Power: 185.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -86.0/+185.0 Inclosure Method: Encapsulated Terminal Type: Wire laad Reliability Indicator: Not established Terminal Length: -1.500 Inches Body Length: -0.109 Inches Body Diameter: -0.109 Inches Sody Length: -0.250 Inches Power Dissipation Rating in Watts: -0.100 Inches Sody Length: -0.250 Inches Sody Length: -0.100 Inches -0.100 In	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Electrical Resistance: 4.750 kilohms Resistance Tolerance in Percent: -1.000/4-1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 185.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -85.0/4-165.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: -1.500 inches Body Length: -0.109 inches Rody Length: -0.250 inches Power Dissipation Rating in Watts: -0.109 rese air Style Designator: Axial terminal each end Test Data Document: 30221-2898650 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure:	
4.750 kilohms  Resistance Tolerance in Percent: -1.000/+1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 165.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -65.0/+165.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: -1.500 inches Body Diameter: -1.0100 inches Body Diameter: -1.09 inches Rody Langth: -2.50 inches Power Dissipation Rating in Watts: -1.010 inches Rody Langth: -2.50 inches Power Dissipation Rating in Watts: -1.010 inches Rody Langth: -2.50 inches Rody Langth: -	
-1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 155.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+165.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document: 30221-2898650 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	4.750 kilohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 165.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+165.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.109 inches Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating in Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document: Sou21-2989650 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing in Shell Life: Na Unit Of Measure: Demilitarization: No Figi:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  185.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  65.0/4 165.0  Inclosure Method: Encapsulated  Terminal Type:  Wire lead  Reliability Indicator: Not established  Terminal Length:  1.500 inches  Body Diameter:  0.109 inches  Body Length:  0.250 inches  Power Dissipation Rating In Watts:  0.100 free air  Style Designator:  Axial terminal each end  Test Data Document:  30221-2289a650 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  Na  Unit Of Measure:   Demilitarization: No  Fig:	-1.000/+1.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  185.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  65.0/4 165.0  Inclosure Method: Encapsulated  Terminal Type:  Wire lead  Reliability Indicator: Not established  Terminal Length:  1.500 inches  Body Diameter:  0.109 inches  Body Length:  0.250 inches  Power Dissipation Rating In Watts:  0.100 free air  Style Designator:  Axial terminal each end  Test Data Document:  30221-2289a650 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  Na  Unit Of Measure:   Demilitarization: No  Fig:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient in Deg Celsius: -65.0/+165.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating in Watts: 0.100 fee air Style Designator: Axial terminal each end Test Data Document: 0.221-289a650 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+165.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.109 inches Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document: 30221-289a650 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life: Via Unit Of Measure:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
-65.0/+165.0 inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.109 inches Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.1500 inches Sover Dissipation Rating In Watts: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document: 30221-289a650 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	165.0
Inclosure Method: Encapsulated Torminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating in Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document: 30221-289a650 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure: Demilitarization: No Fig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document: 30221-289a650 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure: Demilitarization: No Fig:	-65.0/+165.0
Terminal Type:  Wire lead  Reliability Indicator:  Not established  Terminal Length:  1.500 inches  Body Diameter:  0.109 inches  Body Length:  0.250 inches  Power Dissipation Rating In Watts:  0.100 free air  Style Designator:  Axial terminal each end  Test Data Document:  30221-289a650 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Inclosure Method:
Wire lead  Reliability Indicator:  Not established  Terminal Length: 1.500 inches  Body Diameter: 0.109 inches  Body Length: 0.250 inches  Power Dissipation Rating In Watts: 0.100 free air  Style Designator: Axial terminal each end  Test Data Document: 30221-239a650 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fig:	Encapsulated
Reliability Indicator: Not established  Terminal Length: 1.500 inches  Body Diameter: 0.109 inches  Body Length: 0.250 inches  Power Dissipation Rating In Watts: 0.100 free air  Style Designator: Axial terminal each end  Test Data Document: 0.221-289a650 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure: Demilitarization: No Fiig:	Terminal Type:
Not established  Terminal Length:  1.500 inches  Body Diameter:  0.109 inches  Body Length:  0.250 inches  Power Dissipation Rating In Watts:  0.100 free air  Style Designator:  Axial terminal each end  Test Data Document:  30221-289a650 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Wire lead
Terminal Length:  1.500 inches  Body Diameter:  0.109 inches  Body Length:  0.250 inches  Power Dissipation Rating In Watts:  0.100 free air  Style Designator:  Axial terminal each end  Test Data Document:  30221-289a650 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Reliability Indicator:
1.500 inches  Body Diameter: 0.109 inches  Body Length: 0.250 inches  Power Dissipation Rating In Watts: 0.100 free air  Style Designator: Axial terminal each end  Test Data Document: 30221-289a650 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fig:	Not established
Body Diameter:  0.109 inches  Body Length: 0.250 inches  Power Dissipation Rating In Watts: 0.100 free air  Style Designator: Axial terminal each end  Test Data Document: 30221-289a650 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure: Demilitarization: No Fig:	Terminal Length:
0.109 inches  Body Length: 0.250 inches  Power Dissipation Rating In Watts: 0.100 free air  Style Designator: Axial terminal each end  Test Data Document: 30221-289a650 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fig:	1.500 inches
Body Length:  0.250 inches  Power Dissipation Rating In Watts:  0.100 free air  Style Designator:  Axial terminal each end  Test Data Document:  30221-289a650 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Body Diameter:
0.250 inches  Power Dissipation Rating In Watts: 0.100 free air  Style Designator:  Axial terminal each end  Test Data Document: 30221-289a650 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	0.109 inches
Power Dissipation Rating In Watts:  0.100 free air  Style Designator: Axial terminal each end  Test Data Document:  30221-289a650 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Body Length:
0.100 free air  Style Designator:  Axial terminal each end  Test Data Document:  30221-289a650 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	0.250 inches
Style Designator:  Axial terminal each end  Test Data Document:  30221-289a650 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Power Dissipation Rating In Watts:
Axial terminal each end  Test Data Document:  30221-289a650 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	0.100 free air
Test Data Document:  30221-289a650 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:	Style Designator:
30221-289a650 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Axial terminal each end
excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Test Data Document:
Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:	30221-289a650 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
N/a Unit Of Measure: Demilitarization: No Fiig:	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization:  No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0