Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-045-8020

•	
	on Quantity:
1 Dedu	- Cérder
-	r Style:
Cylind	
	bility Indicator:
	stablished
-	v Diameter:
	i inches
-	r Length:
-	2 inches
Actua	ator Type:
Flush	drive with slot-hole
Effec	tive Electrical Rotation In Deg Angular Rotation:
240.0	
Fragi	ility Factor:
Mode	erately delicate
Term	inal Location:
Rear	end
Mour	nting Method:
Tab	
Featu	ures Provided:
Grour	nded contact arm
Elect	rical Resistance Per Section:
200.0	ohms single section
Rota	ry Actuator Travel In Angular Deg:
240.0)
Ambi	ient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0) single section
Powe	er Dissipation Rating Per Section In Watts:
2.0 he	eat sink single section
Resis	stance Tolerance Per Section In Percent:
-10.0/	/+10.0 single section
Actua	ator Travel Control Feature:
Stops	3
Ambi	ient Tempurature In Deg Celsius Per Section At Full Rated Power:
55.0 s	single section
	dard Taper Curve Per Section:
	gle section
	inal Type And Quantity:
	, solder lug
Shelf	
N/a	

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0