NSN 5905-01-045-8948

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-045-8948 **Section Quantity: Body Style:** Cylindrical hole/slot mounted **Reliability Indicator:** Not established **Body Diameter:** 0.375 inches **Shaft Diameter:** 0.375 inches **Shaft Length:** 1.000 inches **Body Length:** 0.781 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 320.0 **Maximum Running Torque:** 2.50 inch-ounces **End Application:** An/fpn-62 **Screw Thread Diameter:** 0.164 inches **Screw Thread Series Designator:** Unc Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Facility Quantity: Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Threaded hole **Electrical Resistance Per Section:** 200.0 ohms single section **Rotary Actuator Travel In Angular Deg:**

330.0

Function Conformity Tolerance Per Section:

-1.00/+1.00 single section

NSN 5905-01-045-8948

Fiig: A002a0

Precision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 100.0 single section **Power Dissipation Rating Per Section In Watts:** 5.9 free air single section **Function Conformity Per Section:** Single section independent linearity **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Actuator Travel Control Feature:** Stops **Function Characteristic Per Section:** Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 0.0 single section **Special Features:** T.O.-31-P52-FPN6 **Terminal Type And Quantity:** 3 turret Shelf Life: N/a **Unit Of Measure:** Demilitarization: No