NSN 5905-01-046-9140

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-046-9140

Section Quantity:
1
Body Style:
Cylindrical servo mounted
Reliability Indicator:
Not established
Pilot Diameter:
0.6250 inches
Pilot Length:
0.0620 inches
Undercut Diameter:
0.625 inches
Undercut Width:
0.0680 inches
Body Diameter:
0.875 inches
Shaft Diameter:
0.1248 inches
Shaft Length:
0.750 inches
Body Length:
1.573 inches
Mounting Lip Diameter:
0.8750 inches
Mounting Lip Depth:
0.0620 inches
Shaft Style:
Round
Shaft Bearing Type:
Ball
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
3600.0
Maximum Starting Torque:
0.40 inch-ounces
Maximum Running Torque:
0.30 inch-ounces
Maximum Stop Torque:
100.00 inch-ounces
Shaft End Play:

0.005 inches

NSN 5905-01-046-9140

Shaft Runout:

Precision Wire Wound Variable Resistor - Page 2 of 3



0.002 inches
Lateral Runout:
0.002 inches
Pilot Diameter Runout:
0.002 inches
Shaft Radial Play:
0.002 inches
Fragility Factor:
Moderately rugged
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Clamp ring
Features Provided:
Humidity proof
Electrical Resistance Per Section:
20.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single section
Power Dissipation Rating Per Section In Watts:
3.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Precious Material And Location:
Terminal surfaces gold
Precious Material:
Gold
Terminal Type And Quantity:
3 tab, solder lug

NSN 5905-01-046-9140

Precision Wire Wound Variable Resistor - Page 3 of 3



Sneit	Lite:
N/a	

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0