Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-046-9144

# Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

# **Reliability Indicator:**

Not established

#### Mounting Hole Diameter:

0.093 inches

#### Shaft Diameter:

0.115 inches

- Shaft Length:
- 0.058 inches

Body Length:

#### 1.250 inches

Body Width:

#### 0.190 inches

**Body Height:** 

0.315 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

#### Effective Electrical Rotation In Deg Angular Rotation:

Between 6120.0 and 9720.0

#### Lateral Distance Between Mounting Hole Centers:

1.000 inches

#### **Mounting Facility Quantity:**

2

#### Terminal Location:

Rear end

#### **Mounting Method:**

Unthreaded hole

#### **Features Provided:**

Humidity proof

#### **Electrical Resistance Per Section:**

10.0 kilohms single section

#### **Rotary Actuator Travel In Angular Deg:**

Between 6120.0 and 9720.0

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

#### Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-250.0/+250.0 single section

# NSN 5905-01-046-9144

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



## **Power Dissipation Rating Per Section In Watts:**

0.75 free air single section

## **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

# Actuator Travel Control Feature:

Clutch

# Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

## Standard Taper Curve Per Section:

A single section

#### **Test Data Document:**

81349-mil-r-39035 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

3 wire lead

## **Specification Data:**

81349-mil-r-39035/1 government specification

Shelf Life:

N/a

---

Unit Of Measure:

**\_** 

# Demilitarization:

No

#### Fiig:

A002a0